



BLACK BEAR COMPANY, INC.

MANUFACTURERS-MARKETERS OF QUALITY LUBRICANTS

27-10 HUNTERS POINT AVE. (49th AVE.)
LONG ISLAND CITY
NEW YORK 11101-4498

MEMBER OF SOCIETY OF TRIBOLOGISTS & LUBRICATION ENGINEERS
MEMBER OF NATIONAL LUBRICATING GREASE INSTITUTE

(718) 784-7330
(800) 660-7330
FAX (718) 392-8283

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURER'S NAME: BLACK BEAR COMPANY, INC.
ADDRESS: 27-10 HUNTERS POINT AVE.
LONG ISLAND CITY, NY 11101

REGULAR PHONE NUMBER: (718) 784-7330
EMERGENCY PHONE NUMBER: (718) 268-2222

CHEMICAL NAME AND SYNONYMS: COMMERCIAL HYDRAULIC OIL

CAS NO.
UN NO.

TRADE NAME AND SYNONYMS: BLACK BEAR WAY LUBRICANT 310 ST

CHEMICAL FAMILY: PETROLEUM HYDROCARBON

FORMULA: COMPLEX MIXTURE OF PETROLEUM
HYDROCARBONS & SELECTED ADDITI.

SHIPPING NAME: DOT: N.A.

IATA: N.A.

SECTION II - HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENT	CAS NO./UN NO.	%	HAZARD DATA
THIS PRODUCT IS NOT CLASSIFIED AS A "HAZARDOUS MATERIAL" IN NORMAL USE AS DEFINED BY OSHA (1910.1200) AND U.S. DEPT OF LABOR REGULATIONS 29 CFR 1915.2(S), § 1916.2(S) AND § 1917.2(R).			

SECTION III - PHYSICAL DATA

BOILING POINT, 760 mm Hg	N.D.	MELTING POINT	N.D.
SPECIFIC GRAVITY (H ₂ O=1)	0.8800	VAPOR PRESSURE (mm Hg at °C)	N.D.
VAPOR DENSITY (AIR=1)	N.D.	SOLUBILITY IN H ₂ O, % BY WT.	N.D.
% VOLATILES BY VOL.	N.D.	EVAPORATION RATE (=1)	N.D.
APPEARANCE AND ODOR		pH (AS IS) pH AT DILUTION	N.D.

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT (TEST METHOD)	435°F. ASTM D92	AUTO IGNITION TEMPERATURE	N.D.	FLAMMABLE LIMITS IN AIR, % BY VOL.	LOWER: N.D. UPPER: N.D.
---------------------------	--------------------	---------------------------	------	------------------------------------	----------------------------

EXTINGUISHING MEDIA: FOAM, DRY CHEMICAL, CO₂, WATER SPRAY OR FOG

SPECIAL FIRE FIGHTING PROCEDURES:

USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREAS.
COOL EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARD: NONE

