



## GC Counting Indicator

With a wide range of features, the GC indicator is ideal for weighing, parts counting, percentage weighing, checkweighing and animal/dynamic weighing. The numeric keypad facilitates unit weight and sample entry, while a large backlit display shows unit weight, total weight and number of pieces. The GC accumulates count totals and alerts the user when a predetermined count is reached. Solid ABS plastic housing wipes down easily, while the wall mount bracket and internal rechargeable battery make the indicator versatile.



# GC Counting Indicator

## Features

- Backlit LCD shows weight, unit weight and count in one convenient location
- Color-coded keys facilitate quick recognition of the most frequently used buttons
- Lightweight design simplifies transport and portability
- RS-232 interface for connection to computers and printers
- Solid ABS housing is durable for industrial uses
- Wall-mount bracket for placing indicator on vertical surface
- Audible overload alarm warns when capacity has been exceeded
- Internal counting resolution 1:600,000 for precision results
- Parts counting with freely selectable sample sizes
- Parts counting optimization automatically refines piece weight as parts are added
- Preset tare function speeds the process of repetitive weighing
- Printouts include date and time for data tracking within Good Laboratory Practices (GLP) guidelines
- Selectable digital filtering helps minimize effects of vibration and disturbances
- Zero-tracking feature ensures display returns to zero reading
- Rechargeable battery included for operation virtually anywhere

## Applications

- Weighing
- Parts counting
- Checkcounting

Model	GC
Capacity Range	Selectable
Resolution	1:80,000
Excitation Voltage	5VDC
Loadcells	4 x 350ohm
Sensitivity	0.15uv/d
Zero Range	0-10mv
Signal Range	0-40mv
Weighing Units	g, kg, lb
Stabilization Time (sec)	2
Interface	RS-232
IP Rating	55
Calibration	External calibration
Display	Backlit LCD with 0.8" / 20mm-high digits
Power Supply	15VDC 800mA adapter / Internal rechargeable battery
Operating Temperature	-10° to 40°C / 14° to 104°F
Housing	ABS
Overall Dim.	10.2"x6.7"x4.5" / 260x170x115mm
Net Weight	4.41lb / 2.00kg

For more than 40 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

## ACCESSORIES

3052010526	In-use wet cover
1120011156	ATP thermal printer
3126011263	Thermal paper for item no. 1120011156-ATP printer
3126011281	Thermal paper for item no. 1120011156-ATP printer (pack of 10)
3074010266	RS-232 cable (null-modem)
3074010507	RS-232 to USB adapter (must order corresponding RS-232 cable)
600002028	Adam DU software

Supplied by:

[www.adamequipment.com](http://www.adamequipment.com)