



GK Indicator

The GK is an affordable indicator with full keypad and smart features, offering a simple user interface for quick operation. Connect the GK to any platform to perform numerous applications, including weighing, percentage weighing, checkweighing, parts counting and animal/dynamic weighing. GK comes with a wall bracket for easy, secure mounting. The GK housing is constructed of ABS plastic, while a backlit LCD features large digits and capacity tracker.



Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Programmable backlight can be set to “always on”, “always off” or “light only when weighing”
- Capacity tracker built into display for easily monitoring possible overloads
- Color-coded keys facilitate quick recognition of the most frequently used buttons
- RS-232 interface for connection to computers and printers
- Solid ABS housing is durable for industrial uses
- Splash-proof housing, keypad and display mean easy cleaning and peace of mind
- Wall-mount bracket for placing indicator on vertical surface
- Checkweighing with audible alarm
- External calibration allows for verification and adjustment with weights
- Parts counting with freely selectable sample sizes
- Parts counting optimization automatically refines piece weight as parts are added

- Preset tare function speeds the process of repetitive weighing
- Printouts include date and time for data tracking within Good Laboratory Practices (GLP) guidelines
- Programmable for counting to a preset number of parts
- Programmable capacity and readability for a variety of applications
- Quick and easy configuration using the keypad
- Selectable digital filtering for animal/dynamic weighing delivers stable results for moving subjects
- Zero-tracking feature ensures display returns to zero reading
- Rechargeable battery included for operation virtually anywhere
- Programmable auto power-off to save energy

Applications

- Weighing
- Parts counting
- Percentage weighing
- Checkweighing
- Checkcounting
- Dynamic / animal weighing

Model	GKa	GKaM
Capacity Range	Selectable	Selectable
Resolution	1:80,000	1:7,500
Excitation Voltage	5VDC	5VDC
Loadcells	4 x 350ohm	4 x 350ohm
Sensitivity	0.15uv/d	0.15uv/d
Zero Range	0-10mv	0-10mv
Signal Range	0-40mv	0-40mv
Weighing Units	kg, lb, lb:oz, oz, N	
Stabilization Time (sec)	2	
Interface	RS-232	
IP Rating	55	
Calibration	External calibration	
Display	Backlit LCD with capacity tracker with 0.8"/ 20mm-high digits	
Power Supply	15VDC 800mA adapter / Internal rechargeable battery	
Operating Temperature	-10° to 40°C / 14° to 104°F	
Housing	ABS	
Overall Dim.	10.2"x6.7"x4.5" / 260x170x115mm	
Net Weight	4.41lb / 2.00kg	
Approvals	N/A	NTEP / Measurement Canada

For more than 40 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

ACCESSORIES

- | | |
|------------|--|
| 3052010526 | In-use wet cover |
| 1120011156 | ATP thermal printer |
| 3126011263 | Thermal paper for item no. 1120011156-ATP printer |
| 3126011281 | Thermal paper for item no. 1120011156-ATP printer (pack of 10) |
| 3074010266 | RS-232 cable (null-modem) |
| 3074010507 | RS-232 to USB adapter (must order corresponding RS-232 cable) |
| 600002028 | Adam DU software |

Supplied by: