



■ Chucks $\varnothing 10''$ and above have additional T-slots

A [in]	Taper Size	B [in]	C [in]	E [in]	E max [in]	F [in]	J [in]	O [in]	T [in]	Weight [lbs]
7.87	L00	4.06	2.13	1.97	1.97	2-3/4	1.59	0.55	3-3/4 - 6	34
7.87	L0	4.45	2.52	1.97	1.97	3-1/4	1.59	0.59	4-1/2 - 6	34
9.84	L00	4.06	2.13	2.56	2.56	2-3/4	1.59	0.55	3-3/4 - 6	57
9.84	L0	4.45	2.52	2.56	2.95	3-1/4	1.59	0.59	4-1/2 - 6	57
9.84	L1	4.96	2.99	2.56	2.95	4-1/8	1.59	0.63	6 - 6	57
12.40	L0	4.72	2.52	3.15	3.35	3-1/4	1.96	0.59	4-1/2 - 6	119
12.40	L1	5.20	2.99	3.15	3.78	4-1/8	1.96	0.63	6 - 6	119
12.40	L2	5.71	3.50	3.15	3.62	5-1/4	1.96	0.87	7-3/4 - 5	119
15.75	L1	5.20	2.99	3.94	4.13	4-1/8	1.96	0.63	6 - 6	154
15.75	L2	5.71	3.50	3.94	4.72	5-1/4	1.96	0.87	7-3/4 - 5	154
19.69	L2	6.06	3.50	4.92	5.31	5-1/4	2.35	0.87	7-3/4 - 5	256

Larger diameters available on page 82-93!

4354

Standard accessories

1 Set of solid reversible jaws

1 Wrench

Spare parts 99-141

Technical data 142-148

Type	Code No.
4354-8" L00	7-854-0841
4354-8" L0	7-854-0842
4354-10" L00	7-854-1041
4354-10" L0	7-854-1042
4354-10" L1	7-854-1043
4354-12" L0	7-854-1242
4354-12" L1	7-854-1243
4354-12" L2	7-854-1244
4354-16" L1	7-854-1643
4354-16" L2	7-854-1644
4354-20" L2	7-854-2044